

PRODUCT DATASHEET

SMART Complete Fitting 4FT Lumbient 18 W 3000-6500 K (ON/OFF)

LL COMPLETE FITTING LIGHT - Smart LED light with ON/OFF built-in microwave motion sensors



AREAS OF APPLICATION

- Parking Areas
- Corridors
- Lobbies
- Garbage Rooms
- Service Rooms
- Low footfall areas

PRODUCT BENEFITS

- Highly efficient LED chip and high IP rating on luminaire front side
- Low maintenance and operation costs due to long lifetime of LED
- Energy savings up to 90% thanks to the smart operational criteria that is due to the built-in smart sensor
- Energy savings thanks to system efficiency of up to 100 lm/W
- Suitable for use in areas with high and low elevation ceilings



PRODUCT FEATURES

- Color rendering index Ra: 80
- Initial color consistency: < 6 SDCM
- CE & RoHS test certificates
- Long lifetime: up to 50,000 h
- Type of protection: IP66

OPERATION

- As the smart built-in sensor detects a movement, light will automatically switch on from off status for until it senses no movement for 30-45 seconds, it will automatically switch off again and vice versa. Through this technology, energy savings would reach up to 90% compared to the use of conventional lighting.



TECHNICAL DATA

Electrical data

| | |
|-----------------|---------|
| Nominal wattage | 18.00 W |
| Nominal voltage | 230 V |
| Power Factor | 0.9 |
| Mains Frequency | 50 Hz |

Photometrical data

| | |
|--------------------------------------|-------------|
| Color temperature | 3000-6500 K |
| Luminous flux | 1800 lm |
| Luminous efficacy | 100 lm/W |
| Standard deviation of color matching | ≤6 sdcn |
| Light color (designation) | Day Light |
| Color rendering index Ra | 80 |

Light technical data

| | |
|------------|------|
| Beam angle | 180° |
|------------|------|

Dimensions

| | |
|--------|-------|
| Length | 1.2 m |
|--------|-------|

Colors & materials

| | |
|---------------|---------------------|
| Body material | Aluminum + PC cover |
| Housing color | White |
| Product color | White |

Temperature & operating conditions

| | |
|---------------------------|---------------|
| Ambient temperature range | -20°C ~ +45°C |
|---------------------------|---------------|

Lifespan

| | |
|----------------------------|----------|
| Lifespan L70 at 25 °C | 50,000 h |
| Number of switching cycles | 100,000 |

Additional product data

| | |
|-------------------|--------------|
| Mounting type | Surface Clip |
| Mounting location | Ceiling/Wall |

Capabilities

| | |
|--------------------|---------------------------|
| Dimmable | No |
| Type of connection | Terminal, 2-Pole (L, N) |
| Technology | Smart LED built-in sensor |

Certificates & standards

| | |
|--------------------|-------|
| Protection class | II |
| Type of protection | IP 66 |

Logistical Data

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|--------------|------------------------------|--------------------------------------|--------------|--------|
|--------------|------------------------------|--------------------------------------|--------------|--------|

